§MAVERICK™ TRAIL DPS™

HIGHLIGHTS

PLATFORM FEATURES

- 50-in. wide
- 90.6-in. wheelbase
- 10-in. front / 10.5-in. rear suspension travel
- 4.5 in. digital display SPORT / ECO™ modes
- Half door (Only for 1000)

SPECIFIC TO DPS PACKAGE

- Dynamic Power Steering (DPS)
- Visco-Lok‡ QE front differential
- 12-in. (30.5 cm) aluminum wheels
- Ergoprint seats with color accents
- Painted color options

AGILE

- Sturdy engine and transmission
- Easy Handling and capabilities
- Front and rear suspension designed for trail riding

ADVENTUROUS

- Meaningful functionalities and versatilities
- Enhanced comfort with Ergo-Lok cockpit
- Build your Maverick Trail that fits your needs

CONFIDENT

- · Perfectly tuned
- Enhanced protection
- More adventure and less maintenance



Can-Am Red 800 / 1000

Triple Black / 1000

Mossy Oak Break-Up Country Camo / 1000

ENGINES	800	1000
Туре	51 hp, Rotax® 799.9 cc, V-twin, liquid cooled	75 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)	
Transmission	Quick Response System(QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P	
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential	
Driving assistance	Electronic Hill Descent Control SPORT / ECO modes	
Power Steering	Dynamic Power Steering (DPS)	

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) travel
Rear Shocks	Twin tube gas charged shocks

BRAKES		
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-niston caliners	

TIRES / WHE	ELS
Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12-in. (30.5 cm) cast-aluminum

DIMENSIONS /	CAPACITIES
LxWxH	118 x 50 x 69.1 in. (300.5 x 127 x 175.5 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	10 in. (25.4 cm)
Estimated Dry Weight	800: 1,331 lb (603.7 kg) 1000: 1,364 lb (618.7 kg)
Chassis / Cage	Profiled cage ROPS approved
Cargo Box Capacity	300 lb (136 kg)
Storage Capacity	Total: 5.3 gal (20.2 L) Glove Box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and Cup holders: 0.8 gal (3.1 L)
Towing capcity	1,500 lb (680 kg)
Fuel Capacity	10 gal (38 L)

FEATURES			
Gauge	4.5 in. (11.4 cm) wide digital display:	Winch	N/A
Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, SPORT / ECO modes, seat belt, diagnostics, clock, battery voltage, engine temperature		Steering Wheel	Adjustable tilt steering
Instrumentation	Lighter type DC outlet in console (20-A)	Protection	Integrated front steel bumper, injected full body skid
Magneto	neto 650-W		plates, half doors (Only for 1000)
Lighting	Two 55 W reflectors and LED tail lights	Hitch Type	2-in hitch receiver

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage



